


Product Name // Inline Cable Connector EXP-0921 Series 7
Contact Socket 13mm-15mm Cable (Yellow Gland)
 [View Product Page](#)

// Product Description:

- ⬢ Inline Cable Connectors for hazardous areas
- ⬢ Water and dustproof to IP68 when mated with compatible connector
- ⬢ Positive fast-acting locking ring - can be turned with a gloved hand
- ⬢ Plug or Socket
- ⬢ 2, 3, 4, 5, 7, 10 Contact with leading Earth on 3, 4, 5, 7 Contact versions, trailing Neutral on 5 Contact version
- ⬢ Screw Terminals
- ⬢ Choice of cable acceptance 7mm-22mm diameter depending on part code (see data for details):
- ⬢ EXP-09 part codes 7mm-15mm diameter
- ⬢ EXP-A9 part codes (large cable version with strain relief clamp) 14mm-22mm diameter
- ⬢ Packs of Cable Glands for differing cable diameters available separately (EXP-0980, EXP-A980)
- ⬢ EXP-0991 heavy duty Sealing Cap available separately to maintain IP rating of unmated connectors
- ⬢ Mate with EXP-09 or EXP-A9 Series Flex and Panel Mount Connectors, as appropriate

// General Information:

Product Display Title:	Inline Cable Connectors for hazardous areas
Product Family:	Circular Power Connectors
Product Series:	EXPlora
Approvals:	UL
Body Material:	Polyester (PET)
Body Material Type:	Plastic Body
Contact Type:	Socket Contact
Coupling Type:	Screw
Current Max:	16A
Diameter Over Coupling Ring Mm:	58mm
Flamability Rating:	UL94V-0
Function:	Inline Cable Connector
Ip Rating:	IP68
Max Cable Entry Size:	15mm
Min Cable Entry Size:	13mm
Max Contact Accomodation Awg:	14AWG
Min Contact Accomodation Awg:	10AWG
Max Contact Accomodation Mm2:	4mm ²
Min Contact Accomodation Mm2:	2.5mm ²
Max Operating Temperature:	+55°C
Min Operating Temperature:	-20°C
Number Of Contacts:	7 Contacts
Voltage Max:	430V

// Product PDF Links
 [EXPlora Series power connectors...](#)
// Product 3D CAD Model Links
 [EXP-0921/07/S3D CAD Model](#)