PX0410/02P/4550 Datasheet




Product Name // Flex Cable Connector PX0410 Series 2 Contact Plug 4.5mm-5.0mm Cable

View Product Page







// Product Description:

- Flex Cable Connector
- Water and dustproof to IP68 when mated with compatible connector
- O Pin or Socket
- 2, 3, 4, 6, 8, 10 or 12 Contact
- O Crimp or Solder Contacts available (supplied separately; use 8A for 2/3 Contact, 5A for 4/6/8 Contact, 1A for 10/12 Contact)
- O Contact insertion and crimp tools available (supplied separately)
- O Choice of cable acceptance 3mm-7mm depending on part code; supplied with Cable Gland and Collet colour coded by size
- PX0481 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with Inline or Panel Mount Connectors PX0401, PX0411, PX0412, PX0413

// General Information:

Product Display Title: Product Family: Product Series: Approvals:

Body Material:
Body Material Type:
Contact Type:
Coupling Type:
Current Max:

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function:

Ip Rating:

Max Cable

Voltage Max:

Max Cable Entry Size: Min Cable Entry Size:

Max Contact Accomodation Awg:
Min Contact Accomodation Awg:
Max Contact Accomodation Mm2:
Min Contact Accomodation Mm2:
Max Operating Temperature:
Min Operating Temperature:
Number Of Contacts:
Rohs Compliant:

Flex Cable Connector Circular Power Connectors 400 Series Buccaneer

UL

IP68

Polyamide (PA) Plastic Body Plug Contact Screw 8A 19.1mm

UL94V-0 Flex Cable Connector

5.0mm
4.5mm
24AWG
20AWG
0.5mm2
0.25mm2
+80°C
-40°C
2 Contacts
Yes
250V



