## PX0410/08P/6065 Datasheet




## Product Name // Flex Cable Connector PX0410 Series 8 Contact Plug 6.0mm-6.5mm Cable

View Product Page







## // Product Description:

- 0 Flex Cable Connector
- 0 Water and dustproof to IP68 when mated with compatible connector
- 0 Pin or Socket
- 0 2, 3, 4, 6, 8, 10 or 12 Contact
- 0 Crimp or Solder Contacts available (supplied separately; use 8A for 2/3 Contact, 5A for 4/6/8 Contact, 1A for 10/12 Contact)
- Contact insertion and crimp tools available (supplied separately)
- 0 Choice of cable acceptance 3mm-7mm depending on part code; supplied with Cable Gland and Collet colour coded by size
- 0 PX0481 Sealing Cap available separately to maintain IP rating of
- Mate with Inline or Panel Mount Connectors PX0401, PX0411, PX0412, PX0413

## // General Information:

**Product Display Title:** 

**Product Family: Product Series:** 

Approvals:

**Body Material:** 

**Body Material Type:** 

Contact Type:

Coupling Type:

**Current Max:** 

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function:

Ip Rating:

Max Cable Entry Size:

Min Cable Entry Size:

Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2:

**Max Operating Temperature:** Min Operating Temperature: **Number Of Contacts:** 

Voltage Max:

Flex Cable Connector

Circular Power Connectors

400 Series Buccaneer

Polyamide (PA)

Plastic Body

Plug Contact

Screw 5A

19.1mm

UL94V-0

Flex Cable Connector

IP68 6.5mm

6.0mm

26AWG

22AWG

0.34mm2

0.14mm2 +80°C

-40°C

8 Contacts

125V

// Product PDF Links





400 Series power connectors wiring...

// Product 3D CAD Model Links