PX0410/10P/6065 Datasheet




Product Name // Flex Cable Connector PX0410 Series 10 Contact Plug 6.0mm-6.5mm Cable

View Product Page







// Product Description:

- Flex Cable Connector
- Water and dustproof to IP68 when mated with compatible connector
- O Pin or Socket
- 2, 3, 4, 6, 8, 10 or 12 Contact
- O Crimp or Solder Contacts available (supplied separately; use 8A for 2/3 Contact, 5A for 4/6/8 Contact, 1A for 10/12 Contact)
- O Contact insertion and crimp tools available (supplied separately)
- O Choice of cable acceptance 3mm-7mm depending on part code; supplied with Cable Gland and Collet colour coded by size
- PX0481 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with Inline or Panel Mount Connectors PX0401, PX0411, PX0412, PX0413

// General Information:

Product Display Title: Product Family: Product Series: Approvals:

Body Material: Body Material Type: Contact Type: Coupling Type:

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function: Ip Rating:

Voltage Max:

Current Max:

Max Cable Entry Size: Min Cable Entry Size:

Max Contact Accomodation Awg:
Min Contact Accomodation Awg:
Max Contact Accomodation Mm2:
Min Contact Accomodation Mm2:
Max Operating Temperature:
Min Operating Temperature:
Number Of Contacts:
Rohs Compliant:

Flex Cable Connector Circular Power Connectors 400 Series Buccaneer

UL

Polyamide (PA) Plastic Body Plug Contact Screw 1A 19.1mm

UL94V-0 Flex Cable Connector

IP68
6.5mm
6.0mm
28AWG
24AWG
0.25mm2
0.08mm2
+80°C
-40°C
10 Contacts
Yes
50V

// Product PDF Links

400 Series power connectors...

400 Series power connectors wiring...

// Product 3D CAD Model Links

⊗ ⊗AD

PX0410/10P/60653D CAD Model