
PX0411/02P/5560 Datasheet



Product Name // Inline Cable Connector PX0411 Series 2 Contact Plug 5.5mm-6.0mm Cable





// Product Description:

- 0 Inline Cable Connector
- 0 Water and dustproof to IP68 when mated with compatible connector
- 0 Pin or Socket
- 0 2, 3, 4, 6, 8, 10 or 12 Contact
- 0 Crimp or Solder Contacts available (supplied separately; use 8A for 2/3 Contact, 5A for 4/6/8 Contact, 1A for 10/12 Contact)
- Contact insertion and crimp tools available (supplied separately)
- 0 Choice of cable acceptance 3mm-7mm depending on part code; supplied with Cable Gland and Collet colour coded by size
- 0 PX0480/1 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with Flex Cable Connectors PX0400, PX0402, PX0410

// General Information:

Product Display Title:

Product Family:

Product Series: Approvals:

Body Material:

Body Material Type:

Contact Type:

Coupling Type:

Current Max:

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function: Ip Rating:

Max Cable Entry Size: Min Cable Entry Size:

Max Contact Accomodation Awg:

Min Contact Accomodation Awg: Max Contact Accomodation Mm2:

Min Contact Accomodation Mm2: **Max Operating Temperature:**

Min Operating Temperature:

Number Of Contacts:

Voltage Max:

Inline Cable Connector

Circular Power Connectors

400 Series Buccaneer

Polyamide (PA)

Plastic Body Plug Contact

Screw

8A

19.1mm

UL94V-0

Inline Cable Connector

IP68

6.0mm 5.5mm

24AWG

20AWG

0.5mm2

0.25mm2 +80°C

-40°C

2 Contacts

250V



400 Series power connectors wiring...

// Product 3D CAD Model Links

