
## PX0411/02S/4550 Datasheet



## Product Name // Inline Cable Connector PX0411 Series 2 Contact Socket 4.5mm-5.0mm Cable

View Product Page



## // Product Description:

- 0 Inline Cable Connector
- 0 Water and dustproof to IP68 when mated with compatible connector
- 0 Pin or Socket
- 0 2, 3, 4, 6, 8, 10 or 12 Contact
- 0 Crimp or Solder Contacts available (supplied separately; use 8A for 2/3 Contact, 5A for 4/6/8 Contact, 1A for 10/12 Contact)
- Contact insertion and crimp tools available (supplied separately)
- 0 Choice of cable acceptance 3mm-7mm depending on part code; supplied with Cable Gland and Collet colour coded by size
- 0 PX0480/1 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with Flex Cable Connectors PX0400, PX0402, PX0410

## // General Information:

**Product Display Title:** 

**Product Family: Product Series:** 

Approvals:

**Body Material:** 

**Body Material Type:** 

Contact Type:

Coupling Type: **Current Max:** 

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function:

Ip Rating:

Max Cable Entry Size:

Min Cable Entry Size:

Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2:

**Max Operating Temperature:** Min Operating Temperature:

**Number Of Contacts:** Voltage Max:

Inline Cable Connector

Circular Power Connectors 400 Series Buccaneer

Polyamide (PA)

Plastic Body Socket Contact

Screw

8A

19.1mm UL94V-0

Inline Cable Connector

IP68 5.0mm

4.5mm

24AWG

20AWG

0.5mm2 0.25mm2

+80°C

-40°C

2 Contacts

250V



// Product 3D CAD Model Links