
PX0460/A Datasheet



Product Name // Front Panel Mount Leaded USB Connector PX0460 Series Sealed A Socket Front of Panel to 5 Way Crimp Connector with exposed braid

View Product Page





// Product Description:

- O Front Panel Mounting Leaded Connector
- O Water and dustproof to IP68 when mated with compatible connector
- O Sealed Standard USB socket to 125mm long cable terminated in 5 way crimp connector for use with PC header (available separately, part code 14191, 14192)
- O PX0843/A has Sealed Standard USB Type A socket on front of panel
- O PX0843/B has Sealed Standard USB Type B socket on front of panel
- O PX0460/A and PX0460/B are identical to PX0843/A and PX0843/B but with exposed braid for use with PX0465 Screening Can (available separately)
- O PX0733 Sealing Cap available separately to maintain IP rating of unmated connectors
- O Mate with PX0840, PX0841 USB Cables

// General Information:

Product Display Title: Product Family: **Product Series: Body Material:** Body Material Type: Contact Type: Coupling Type: **Current Max:** Data Cable Type: Diameter Over Coupling Ring Mm: Flamability Rating: Function: Ip Rating: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Voltage Max:

Front Panel Mounting Leaded Connector **Circular Data Connectors** Standard Buccaneer - USB Polyester (PE) - Glass Filled Plastic Body Socket Contact Screw 1A USB Sealed A Socket to 5 Way Crimp 38.1mm UL94V-0 Front Panel Mount Connector IP68. IP69K +70°C 0°C 4 Contacts 30V

// Product PDF Links

Standard Series USB connectors..

// Product 3D CAD Model Links

PX0460/A3D CAD Model