
PX0460/A3 Datasheet



Product Name // Front Panel Mount Leaded USB 3.0 Connector PX0460 Series Sealed A Socket Front of Panel to 10 Way Crimp Connector with exposed braid

View Product Page



// Product Description:

- O Front Panel Mounting Leaded Connector
- O Water and dustproof to IP68 when mated with compatible connector
- O Sealed Standard USB 3.0 Type A socket to 200mm long cable terminated in 5 way crimp connector to use with PC header
- Identical to PX0843/A3 but with exposed braid for use with PX0465 Screening Can (available separately)
- O PX0733 Sealing Cap available separately to maintain IP rating of unmated connectors
- O Mate with PX0840, PX0841 USB Cables

// General Information:

Product Display Title: **Product Family: Product Series:** Body Colour: Body Material: Body Material Type: Contact Type: Coupling Type: Current Max: Data Cable Type: Diameter Over Coupling Ring Mm: Flamability Rating: Function: Ip Rating: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Rohs Compliant: Voltage Max:

Front Panel Mounting Leaded Connector **Circular Data Connectors** Standard Buccaneer - USB Black Polyester (PE) - Glass Filled Plastic Body Socket Contact Screw 1A USB 3.0 Sealed A Socket to 10 Way Crimp 38.1mm UL94V-0 Front Panel Mount Connector IP68, IP69K +70°C 0°C 9 Contacts Yes 5V

// Product PDF Links

Standard Series USB connectors...

// Product 3D CAD Model Links

PX0460/A33D CAD Model