
## **PX0805 Datasheet**



## Product Name // Mini Series Panel Mount Connector Body With Sealing Cap Retaining Clip

View Product Page





## // Product Description:

- Mini Series of modular connectors
- Water and dustproof to IP68 when mated with compatible connector
- O Choose type of connector body:
- Part codes prefixed PX0800 Flex Cable Connectors (mate with PX0801 Inline Cable Connectors, PX08 Mini Series Panel Mount Connectors), optionally choose cable acceptance
- Part codes prefixed PX0801 Inline Cable Connectors (mate with PX0800 Flex Cable Connectors), optionally choose cable acceptance
- Part codes prefixed PX0802, PX0803, PX0804, PX0805 Panel Mount Connectors (mate with PX08 Mini Series Flex Cable Connectors)
- Choose type of contacts from Screw Terminal, Solder/Crimp Contacts, BNC
- O Choose number of connector Contacts and select appropriate connector insert/contact carrier:

- O Screw Terminal inserts available separately in 2, 3, 4, 6 Contact, Pin or Socket
- O Solder, Crimp Contact carriers available separately in 3, 8
  Contact; select appropriate Contact Pins or Sockets and
  Polarising/Blanking Pins, Contact Insertion Tool, Crimping Tool
  as required (all available separately)
- O BNC Plug or Socket insert available separately in 50 Ohm, 75 Ohm versions for all connector body styles except PX0803
- PX0800, PX0801 Flex and Inline Cable Connector bodies have a choice of cable acceptance 3.5mm-9mm diameter depending on part code (see data for details)
- Pack of Cable Glands for differing cable sizes also available separately (PX0812)
- Sealing Caps (available separately) can be used to maintain IP rating of unmated connectors:
- O PX0811 fits PX0800 Flex Cable Connector
- O PX0810 fits all other connectors in the PX08 Mini Series

## // General Information:

Product Display Title: Product Family: Product Series:

Approvals:
Body Material:
Body Material Type:

Coupling Type:

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function: Ip Rating:

Max Operating Temperature:
Min Operating Temperature:

Mini Series of modular connectors

Circular Power Connectors

Mini Buccaneer

UL94V-0

Polyamide (PA) Plastic Body Screw 26mm

Rear Panel Mount Connector Body

IP68 +70°C -20°C



