
# PX0911/05/P Datasheet



## Product Name // Flex Cable Connector PX0911 Series 5 Contact Plug 13mm-15mm Cable (Yellow Gland)

View Product Page



### // Product Description:

- O Flex Cable Connectors
- O Water and dustproof to IP68 when mated with compatible connector
- O Positive fast-acting locking ring can be turned with a gloved hand
- O Plug or Socket
- 2, 3, 4, 5, 7, 10 Contact with leading Earth on 3, 4, 5, 7 Contact versions, trailing Neutral on 5 Contact version
- O Screw Terminals

- Choice of cable acceptance 7mm-22mm diameter depending on part code (see data for details):
- O PX09 part codes 7mm-15mm diameter
- PXA9 part codes (large cable version with strain relief clamp) 14mm-22mm diameter
- Packs of Cable Glands for differing cable diameters available separately (PX0980, PXA980)
- O PX0960/PX0990 Sealing Caps available separately to maintain IP rating of unmated connectors
- Mate with PX09 or PXA9 Series Flex and Panel Mount Connectors, as appropriate

#### // General Information:

**Product Display Title: Product Family: Product Series:** Approvals: Body Material: Body Material Type: Contact Type: Coupling Type: Current Max: Diameter Over Coupling Ring Mm: Flamability Rating: Function: Ip Rating: Max Cable Entry Size: Min Cable Entry Size: Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Voltage Max:

Flex Cable Connectors **Circular Power Connectors** 900 Series Buccaneer UL Polyamide (PA) Plastic Body Plug Contact Screw 32A 58mm UL94V-0 Flex Cable Connector IP68 15mm 13mm 13AWG 10AWG 4mm2 2.6mm2 +85°C -40°C 5 Contacts 600V

#### // Product PDF Links

900 Series power connectors...

900 Series power connectors wiring..

// Product 3D CAD Model Links

PX0911/05/P3D CAD Model