
PX0941/05/S Datasheet



Contact Socket

🚯 View Product Page

bulgin



// Product Description:

- O Flange Mount Connector
- O Water and dustproof to IP68 when mated with compatible connector
- O Positive fast-acting locking ring can be turned with a gloved hand
- O Plug or Socket
- 2, 3, 4, 5, 7, 10 Contact with leading Earth on 3, 4, 5, 7 Contact versions, trailing Neutral on 5 Contact version
- O Supplied with high grade sealing gasket
- Supplied with sealing grommets for panel fixing screws (M6 thread recommended)
- Additional Bulkhead Adaptor Moulding available separately (PX0950) to enable connector angle of 45 or 90 degrees
- O PX0970/PX0992 Sealing Cap available separately to maintain IP rating of unmated connectors
- O Mate with PX0911 and PXA911 Series Flex Connectors

// General Information:

Product Display Title: Product Family: Product Series: Approvals: **Body Material: Body Material Type:** Contact Type: Coupling Type: **Current Max:** Diameter Over Coupling Ring Mm: Flamability Rating: Function: Ip Rating: Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Voltage Max:

Flange Mount Connector **Circular Power Connectors** 900 Series Buccaneer CSA Polyamide (PA) **Plastic Body** Socket Contact Screw 25A 58mm UL94V-0 Flange Mount Connector IP68 14AWG 10AWG 4mm2 2.5mm2 +85°C -40°C 5 Contacts 600V

// Product PDF Links

900 Series power connectors...

900 Series power connectors wiring...

// Product 3D CAD Model Links

PX0941/05/S3D CAD Model

Have a question or project enquiry you'd like to talk to us about?