
# PXA911/04/P Datasheet



# Product Name // Flex Cable Connector Large Cable PXA911 Series 4 Contact Plug 20mm-22mm Cable (Yellow Gland)







#### // Product Description:

- Flex Cable Connectors
- Water and dustproof to IP68 when mated with compatible connector
- Positive fast-acting locking ring can be turned with a gloved hand
- O Plug or Socket
- Q 2, 3, 4, 5, 7, 10 Contact with leading Earth on 3, 4, 5, 7 Contact versions, trailing Neutral on 5 Contact version
- Screw Terminals

- Choice of cable acceptance 7mm-22mm diameter depending on part code (see data for details):
- O PX09 part codes 7mm-15mm diameter
- PXA9 part codes (large cable version with strain relief clamp)
  14mm-22mm diameter
- Packs of Cable Glands for differing cable diameters available separately (PX0980, PXA980)
- PX0960/PX0990 Sealing Caps available separately to maintain
  IP rating of unmated connectors
- Mate with PX09 or PXA9 Series Flex and Panel Mount Connectors, as appropriate

#### / General Information:

Product Display Title: Product Family:

Product Series:

Approvals:

Body Material: Body Material Type:

Contact Type:

Coupling Type:

Current Max:

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function:

Ip Rating:

Max Cable Entry Size:

Min Cable Entry Size:

Max Contact Accomodation Awg: Min Contact Accomodation Awg:

Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature:

Number Of Contacts: Voltage Max:

Flex Cable Connectors

Circular Power Connectors

900 Series Buccaneer

UL

Polyamide (PA)

Plastic Body

Plug Contact

Screw

32A 58mm

UL94V-0

Flex Cable Connector

IP68

22mm 20mm

13AWG

10AWG

4mm2 2.6mm2

+85°C

-40°C

4 Contacts 600V

## // Product PDF Links



900 Series power connectors wiring...

## // Product 3D CAD Model Links

PXA911/04/P3D CAD Model

