
PXF6051CAH Datasheet



Product Name // 200 M, OS1 Single Mode, Cabled, Inline fiber connector

View Product Page



// Product Description:

- O Inline Fiber Connector to LC type connector
- O Sealed to IP66, IP68, IP69K when mated with compatible connector
- O no cable options, or pre-terminated from 5M 450M available
- O Duplex LC type fiber connector

- O Choices of OS1, OM1 and OM3 cables for single or multimode
- O PXP6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- O Mate with flex fiber connector PXF6050

// General Information:

Product Display Title: Product Family: Product Series: Body Material: Contact Type: Coupling Type: Diameter Over Coupling Ring Mm: Fibre Mode: Flamability Rating: Function: Ip Rating: Max Operating Temperature: Min Operating Temperature: Inline Fiber Connector to LC type Connector Circular Fiber Connectors 6000 Series - Duplex LC Fiber Buccaneer Polyamide (PA) LC Fiber 30 Degree coupling 32mm OS1 UL94V-0 Inline to Double LC Connector Double Ended Fiber Cable IP66, IP68, IP69K +70°C -25°C

// Product PDF Links

6000 Series Fiber connectors...

// Product 3D CAD Model Links

PXF6051CAH3D CAD Model