PXM6010/02S/ST/0709/SN Datasheet



Product Name // Flex Cable Connector PXM6010 Series 2 Contact Socket Screw Termination (contacts supplied fitted) 7mm-9mm Cable (Yellow Gland) Metal Body With Braid Termination





// Product Description:

- Flex Cable Connectors
- Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- Socket
- 2 Contacts
- O Screw contacts supplied fitted

- O Metal Body With Braid Termination
- O Cable acceptance 7mm-9mm diameter
- Q Gland Pack PXP6088 available separately to accommodate all sizes
- PXM6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with PXM6011 Series Inline and PXM6012 Series Front Panel Mount Connectors

// General Information:

Product Display Title:

Product Family:

Product Series:

Approvals:

Body Colour:

Body Material: Body Material Type:

Contact Type:

Coupling Type:

Current Max:
Diameter Over Coupling Ring Mm:

Function:

Insulation Resistance:

Ip Rating:

Max Cable Entry Size: Min Cable Entry Size:

Max Contact Accompdation Awg:
Min Contact Accompdation Awg:

Min Contact Accomodation Awg:
Max Contact Accomodation Mm2:
Min Contact Accomodation Mm2:
Max Operating Temperature:
Min Operating Temperature:
Number Of Contacts:

Salt Spray Corrosion Test:

Voltage Max:

Rohs Compliant:

Flex Cable Connectors

Circular Power Connectors

6000 Series Buccaneer

UL

Metallic Grey

Brass

Metal Body With Braid Termination Socket Contact

Push-Twist 16A, 11A

32mm

Flex Cable Connector $>10^6 M\Omega$ @500V DC

IP66, IP68, IP69K

P66, 1P68, 1P691

9mm 7mm 14AWG

14AWG 2.5mm2 2.5mm2 +120°C

-40°C

2 Contacts

Yes

EN60068-2-11 Test Ka Salt Mist

277V

// Product PDF Links 6000 Series power connectors... 6000 Series metal body power...



Click Here To Contact Us