PXM6010/03S/ST/0507/SN Datasheet

Product Name // Flex Cable Connector PXM6010 Series 3 Contact Socket Screw Termination (contacts supplied fitted) 5mm-7mm Cable (White Gland) Metal Body With Braid Termination





// Product Description:

- O Flex Cable Connectors
- O Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- O Socket
- O 3 Contacts
- O Screw contacts supplied fitted

- O Metal Body With Braid Termination
- O Cable acceptance 5mm-7mm diameter
- O Gland Pack PXP6088 available separately to accomodate all sizes
- O PXM6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- O Mate with PXM6011 Series Inline and PXM6012 Series Front Panel Mount Connectors

// General Information:

Product Display Title: Product Family: Product Series: Approvals: Body Colour: Body Material: **Body Material Type:** Contact Type: **Coupling Type: Current Max:** Diameter Over Coupling Ring Mm: Function: Insulation Resistance: Ip Rating: Max Cable Entry Size: Min Cable Entry Size: Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: **Rohs Compliant:** Salt Spray Corrosion Test: Voltage Max:

Flex Cable Connectors **Circular Power Connectors** 6000 Series Buccaneer UL Metallic Grey Brass Metal Body With Braid Termination Socket Contact Push-Twist 16A, 11A 32mm Flex Cable Connector $>10^6 M\Omega$ @500V DC IP66, IP68, IP69K 7mm 5mm 14AWG 14AWG 2.5mm2 2.5mm2 +120°C -40°C 3 Contacts Yes EN60068-2-11 Test Ka Salt Mist 277V



// Product 3D CAD Model Links

PXM6010/03S/ST/0507/SN3D CAD Model

Have a question or project enquiry you'd like to talk to us about?

Click Here To Contact Us