## PXM6010/22P/CR/0405/SN Datasheet bulgin



Product Name // Flex Cable Connector PXM6010 Series 22 **Contact Plug Crimp/Solder Termination (contacts available** separately) 4mm-5mm Cable (Dark Grey Gland) Metal Body With Braid Termination





## // Product Description:

- Flex Cable Connectors 0
- 0 Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 0 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- 0 Plug
- O 22 Contacts
- 0 Crimp/solder termination with contacts and fitting tool available separately
- 0 Metal Body With Braid Termination
- 0 Cable acceptance 4mm-5mm diameter
- Gland Pack PXP6088 available separately to accomodate all sizes
- PXM6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with PXM6011 Series Inline and PXM6012 Series Front Panel Mount Connectors

## // General Information:

**Product Display Title:** 

**Product Family: Product Series:** 

Approvals:

**Body Colour:** 

**Body Material: Body Material Type:** 

Contact Type:

Coupling Type:

**Current Max:** 

Diameter Over Coupling Ring Mm:

Function:

Insulation Resistance:

Ip Rating:

Max Cable Entry Size:

Min Cable Entry Size:

Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature:

Min Operating Temperature: **Number Of Contacts:** 

Salt Spray Corrosion Test:

Voltage Max:

Rohs Compliant:

Flex Cable Connectors

Circular Power Connectors

6000 Series Buccaneer

UL

Metallic Grey

**Brass** 

Metal Body With Braid Termination

Plug Contact Push-Twist 1.5A, 2A, 3A

32mm

Flex Cable Connector >106MΩ @500V DC

IP66, IP68, IP69K

5mm 26AWG 26AWG 0.14mm2 0.14mm2 +120°C -40°C

22 Contacts

EN60068-2-11 Test Ka Salt Mist



