
PXM6011/02S/ST/0709 Datasheet



Product Name // Inline Cable Connector PXM6011 Series 2 **Contact Socket Screw Termination (contacts supplied** fitted) 7mm-9mm Cable (Yellow Gland) Metal Body No Braid **Termination**





// Product Description:

- 0 Inline Cable Connectors
- 0 Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 0 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- 0 Socket
- 0 2 Contacts
- 0 Screw contacts supplied fitted

- 0 Metal Body No Braid Termination
- 0 Cable acceptance 7mm-9mm diameter
- O Gland Pack PXP6088 available separately to accomodate all
- O PXM6082 Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with PXM6010 Series Flex Connectors

// General Information:

Product Display Title:

Product Family:

Product Series: Approvals:

Body Colour:

Body Material: Body Material Type:

Contact Type:

Coupling Type:

Current Max:

Diameter Over Coupling Ring Mm:

Function:

Insulation Resistance:

Ip Rating:

Max Cable Entry Size: Min Cable Entry Size:

Max Contact Accomodation Awg:

Min Contact Accomodation Awg:

Max Contact Accomodation Mm2: Min Contact Accomodation Mm2:

Max Operating Temperature:

Min Operating Temperature:

Number Of Contacts: Rohs Compliant:

Salt Spray Corrosion Test:

Voltage Max:

Inline Cable Connectors

Circular Power Connectors 6000 Series Buccaneer

UL

Metallic Grey

Brass

Metal Body No Braid Termination

Socket Contact

Push-Twist 16A, 11A

32mm

Inline Cable Connector

 $>10^6 M\Omega$ @500V DC

IP66, IP68, IP69K

9_{mm}

7_{mm}

14AWG

14AWG

2.5mm2

2.5mm2

+120°C -40°C

2 Contacts

EN60068-2-11 Test Ka Salt Mist

277V





Click Here To Contact Us