
PXM6011/03P/ST/0405 Datasheet



Product Name // Inline Cable Connector PXM6011 Series 3 **Contact Plug Screw Termination (contacts supplied fitted)** 4mm-5mm Cable (Dark Grey Gland) Metal Body No Braid **Termination**





// Product Description:

- 0 Inline Cable Connectors
- 0 Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 0 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- 0 Plug
- 0 3 Contacts
- 0 Screw contacts supplied fitted

- 0 Metal Body No Braid Termination
- 0 Cable acceptance 4mm-5mm diameter
- O Gland Pack PXP6088 available separately to accomodate all
- O PXM6082 Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with PXM6010 Series Flex Connectors

// General Information:

Product Display Title:

Product Family:

Product Series: Approvals:

Body Colour: Body Material:

Body Material Type:

Contact Type: Coupling Type:

Current Max:

Diameter Over Coupling Ring Mm:

Function:

Insulation Resistance:

Ip Rating:

Max Cable Entry Size: Min Cable Entry Size:

Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2:

Max Operating Temperature: Min Operating Temperature: **Number Of Contacts:**

Salt Spray Corrosion Test:

Voltage Max:

Rohs Compliant:

Inline Cable Connectors

Circular Power Connectors 6000 Series Buccaneer

UL

Metallic Grey

Brass

Metal Body No Braid Termination Plug Contact

Push-Twist 16A, 11A

32mm

Inline Cable Connector

 $>10^6 M\Omega$ @500V DC

IP66, IP68, IP69K

5_{mm} 4mm 14AWG 14AWG

2.5mm2 2.5mm2 +120°C -40°C

3 Contacts

EN60068-2-11 Test Ka Salt Mist

277V

// Product PDF Links 6000 Series power connectors.

