## PXM6011/03P/ST/0507 Datasheet



Product Name // Inline Cable Connector PXM6011 Series 3 **Contact Plug Screw Termination (contacts supplied fitted)** 5mm-7mm Cable (White Gland) Metal Body No Braid **Termination** 





## // Product Description:

- 0 Inline Cable Connectors
- 0 Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 0 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- 0 Plug
- 0 3 Contacts
- 0 Screw contacts supplied fitted

- 0 Metal Body No Braid Termination
- 0 Cable acceptance 5mm-7mm diameter
- O Gland Pack PXP6088 available separately to accomodate all
- O PXM6082 Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with PXM6010 Series Flex Connectors

## // General Information:

**Product Display Title:** 

**Product Family: Product Series:** 

Approvals:

**Body Colour:** 

**Body Material: Body Material Type:** 

Contact Type:

Coupling Type:

**Current Max:** 

Diameter Over Coupling Ring Mm:

Function:

Insulation Resistance:

Ip Rating:

Max Cable Entry Size: Min Cable Entry Size:

Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: **Number Of Contacts:** 

Salt Spray Corrosion Test:

Voltage Max:

**Rohs Compliant:** 

Inline Cable Connectors

Circular Power Connectors 6000 Series Buccaneer

UL

Metallic Grey

**Brass** 

Metal Body No Braid Termination Plug Contact

Push-Twist 16A, 11A

32mm

Inline Cable Connector  $>10^6 M\Omega$  @500V DC

IP66, IP68, IP69K

7<sub>mm</sub>


5<sub>mm</sub> 14AWG 14AWG 2.5mm2 2.5mm2 +120°C

-40°C 3 Contacts

EN60068-2-11 Test Ka Salt Mist

277V

## // Product PDF Links 6000 Series power connectors.



Click Here To Contact Us