
PXM6034/B Datasheet



Product Name // Rewireable Flex Connector PXM6034 **Series 4mm-7mm Cable Metal Body**







// Product Description:

- Rewireable Flex Cable Connectors
- 0 Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 0 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- O Supplied with shielded RJ45 plug
- O Choice of cable acceptance depending on part code:
- O Part codes suffixed /A have cable glands optimised for PUR jacket cable to maintain CAT5e performance
- Part codes suffixed /B accept cable 4mm-7mm diameter
- O Choice of body material depending on part code:
- O Plastic body (part codes prefixed PXP)
- O Metal body (part codes prefixed PXM)
- O PXP6081/PXM6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with PXP6033TP, PXP6033TP/E, PXM6033TP Front Panel Mount CAT5e Couplers

General Information:

Product Display Title:

Product Family:

Product Series: Body Material:

Body Material Type:

Contact Type:

Coupling Type:

Current Max:

Diameter Over Coupling Ring Mm:

Ethernet Category:

Function:

Ip Rating:

Max Cable Entry Size: Min Cable Entry Size:

Max Operating Temperature: Min Operating Temperature: **Number Of Contacts:**

Voltage Max:

Rewireable Flex Cable Connectors

Circular Data Connectors

6000 Series - Ethernet Buccaneer

Brass - Nickel Plated

Metal Body

Plug Contact

Push-Twist

1.5A

32mm

Cat 5e

Flex Cable Connector

IP66, IP68, IP69K

7mm

4mm +70°C

-20°C

8 Contacts

42V

// Product PDF Links

6000 Series Ethernet connectors...

6000 Series Ethernet connectors...

// Product 3D CAD Model Links

PXM6034/B3D CAD Model