


Product Name // Plastic Rear Panel Mount USB A Female to USB A Male Cable Assembly 3m
 [View Product Page](#)

// Product Description:

- ⬢ IP67 Female USB A to Male USB A
- ⬢ IP67 when mated or fitted with Sealing Cap PXP0024, PXM0024
- ⬢ Plastic and metal Sealing Caps available
- ⬢ Mates with Plastic Flex USB A to USB A Cable Assembly PXP0020
- ⬢ USB 2.0 Performance
- ⬢ Length 3m

// General Information:

Product Display Title:	Rear Panel Mount / Leaded Connector
Product Family:	Circular Data Connectors
Product Series:	20 Series USB
Body Colour:	Black
Body Material:	PVC
Body Material Type:	Plastic Body
Cable Length:	3m
Contact Pin Material:	Copper, Gold plated
Contact Type:	Socket Contact
Coupling Type:	Screw
Data Cable Type:	USB 2.0 Sealed A Socket to Standard A Plug
Durability:	1500
Fixing Nut Material:	Plastic
Flamability Rating:	UL94V-0
Function:	Rear Panel Mount Connector
Ip Rating:	IP67
Max Operating Temperature:	80°C
Min Operating Temperature:	-10°C
Max Panel Thickness:	3.5-5mm
Number Of Contacts:	4 Contacts
Panel Cut Out:	20.8mm x 19.4mm
Rohs Compliant:	Yes
Sheath Colour:	Black
Sheath Material:	PVC
Thread Size:	13/16-28UN 2A
Voltage Max:	5V

// Product PDF Links
 [20 Series USB Waterproof product...](#)
// Product 3D CAD Model Links
 [PXP0023/A/3M00/A3D CAD Model](#)