
PXP6010/22S/CR/0910 Datasheet



Product Name // Flex Cable Connector PXP6010 Series 22 **Contact Socket Crimp/Solder Termination (contacts** available separately) 9mm-10mm Cable (Light Grey Gland) **Plastic Body**





// Product Description:

- 0 Flex Cable Connectors
- 0 Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 0 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- 0 Socket
- 0 22 Contacts
- 0 Crimp/solder termination with contacts and fitting tool available separately
- 0 Plastic Body
- 0 Cable acceptance 9mm-10mm diameter
- Ó Gland Pack PXP6088 available separately to accomodate all
- 0 PXP6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with PXP6011 Series Inline, PXP6012 and PXP6014 Series Front Panel Mount Connectors

// General Information:

Product Display Title:

Product Family: Product Series:

Approvals:

Body Colour:

Body Material:

Body Material Type: Contact Type:

Coupling Type:

Current Max:

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function:

Insulation Resistance:

Ip Rating:

Max Cable Entry Size:

Min Cable Entry Size:

Max Contact Accomodation Awg: Min Contact Accomodation Awg:

Max Contact Accomodation Mm2:

Min Contact Accomodation Mm2:

Max Operating Temperature: Min Operating Temperature:

Number Of Contacts:

Rohs Compliant:

Salt Spray Corrosion Test:

Voltage Max:

Flex Cable Connectors

Circular Power Connectors

6000 Series Buccaneer

Polycarbonate/Polybutylene Terephthalate (PC/PBT)

Plastic Body

Socket Contact Push-Twist

1.5A, 2A, 3A

32mm

UL94V-0 Flex Cable Connector

>106MΩ @500V DC

IP66, IP68, IP69K

10mm

26AWG

26AWG 0.14mm2

0.14mm2

+120°C -40°C

22 Contacts

EN60068-2-52 Test Kb Salt Mist (Cyclic) Marine Severity Level 1

60V







// Product 3D CAD Model Links

Click Here To Contact Us

