Circular Power Connectors / 6000 Series Buccaneer


PXP6011/03P/ST/0709 Datasheet



View Product Page

Product Name // Inline Cable Connector PXP6011 Series 3 Contact Plug Screw Termination (contacts supplied fitted) 7mm-9mm Cable (Yellow Gland) Plastic Body





// Product Description:

- O Inline Cable Connectors
- O Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- O 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- O Plug
- O 3 Contacts
- O Screw contacts supplied fitted

- O Plastic Body
- O Cable acceptance 7mm-9mm diameter
- O Gland Pack PXP6088 available separately to accomodate all sizes
- O PXP6082 Sealing Cap available separately to maintain IP rating of unmated connectors
- O Mate with PXP6010 Series Flex Connectors

// General Information:

Product Display Title:	Inline Cable Connectors
Product Family:	Circular Power Connectors
Product Series:	6000 Series Buccaneer
Approvals:	UL
Body Colour:	Grey
Body Material:	Polycarbonate/Polybutylene Terephthalate (PC/PBT)
Body Material Type:	Plastic Body
Contact Type:	Plug Contact
Coupling Type:	Push-Twist
Current Max:	16A, 11A
Diameter Over Coupling Ring Mm:	32mm
Flamability Rating:	UL94V-0
Function:	Inline Cable Connector
Insulation Resistance:	>10 ⁶ MΩ @500V DC
Ip Rating:	IP66, IP68, IP69K
Max Cable Entry Size:	9mm
Min Cable Entry Size:	7mm
Max Contact Accomodation Awg:	14AWG
Min Contact Accomodation Awg:	14AWG
Max Contact Accomodation Mm2:	2.5mm2
Min Contact Accomodation Mm2:	2.5mm2
Max Operating Temperature:	+120°C
Min Operating Temperature:	-40°C
Number Of Contacts:	3 Contacts
Rohs Compliant:	Yes
Salt Spray Corrosion Test:	EN60068-2-52 Test Kb Salt Mist (Cyclic) Marine Severity Level 1
Voltage Max:	277V

// Product PDF Links

6000 Series power connectors...

6000 Series metal body power...

// Product 3D CAD Model Links

PXP6011/03P/ST/07093D CAD Model

Have a question or project enquiry you'd like to talk to us about?

Click Here To Contact Us