PXP6040/A/3M00 Datasheet



Product Name // Plastic Body Overmoulded USB Cable PXP6040 Series Standard B Plug to Sealed A Plug 3M Cable

🚯 View Product Page



// Product Description:

- O Pre-Wired Plastic Body Overmoulded USB V2.0 Cable
- O Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- O Two versions:
- O Part codes containing /A are Standard USB Type B plug to Sealed Standard USB Type A plug
- O Part codes containing /B are Standard USB Type A plug to Sealed Standard USB Type B plug
- O Choice of cable lengths depending on part code
- O PXP6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- O Mate with 6000 Series Plastic Body USB Panel Mount Connectors

// General Information:

Product Display Title: Product Family: **Product Series:** Approvals: Body Material: Contact Type: Coupling Type: Current Max: Data Cable Type: Diameter Over Coupling Ring Mm: Flamability Rating: Function: Ip Rating: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Voltage Max:

Pre-Wired Plastic Body Overmoulded USB V2.0 Cable Circular Data Connectors 6000 Series - USB Buccaneer CSA, UL, VDE Polycarbonate/Polybutylene Terephthalate (PC/PBT) Plug Contact Push-Twist 1A Standard B Plug to Sealed A Plug 32mm UI 94V-0 Flex to Standard Connector Double Ended Cable IP66, IP68, IP69K +120°C -40°C 4 Contacts 30V

// Product PDF Links

6000 Series USB connectors product...

// Product 3D CAD Model Links

PXP6040/A/3M003D CAD Model