


PXP6041/AB/5M00 Datasheet

Product Name // Plastic Body Overmoulded USB Cable
PXP6041 Series Sealed A Plug to Sealed B Plug 5M Cable

[View Product Page](#)



// Product Description:

- ⊕ Pre-Wired Plastic Body Overmoulded USB V2.0 Cable
- ⊕ Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- ⊕ 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- ⊕ Sealed Standard USB Type A plug to Sealed Standard USB Type B plug
- ⊕ Choice of cable lengths depending on part code
- ⊕ PXP6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- ⊕ Mate with 6000 Series Plastic Body USB Panel Mount Connectors

// General Information:

| | |
|---------------------------------|---|
| Product Display Title: | Pre-Wired Plastic Body Overmoulded USB V2.0 Cable |
| Product Family: | Circular Data Connectors |
| Product Series: | 6000 Series - USB Buccaneer |
| Approvals: | CSA, UL, VDE |
| Body Material: | Polycarbonate/Polybutylene Terephthalate (PC/PBT) |
| Contact Type: | Plug Contact |
| Coupling Type: | Push-Twist |
| Current Max: | 1A |
| Data Cable Type: | Sealed A Plug to Sealed B Plug |
| Diameter Over Coupling Ring Mm: | 32mm |
| Flamability Rating: | UL94V-0 |
| Function: | Flex to Flex Connector Double Ended Cable |
| Ip Rating: | IP66, IP68, IP69K |
| Max Operating Temperature: | +120°C |
| Min Operating Temperature: | -40°C |
| Number Of Contacts: | 4 Contacts |
| Voltage Max: | 30V |

// Product PDF Links

[6000 Series USB connectors product...](#)

// Product 3D CAD Model Links

[PXP6041/AB/5M003D CAD Model](#)



Have a question or project enquiry
you'd like to talk to us about?



[Click Here To Contact Us](#)