
PXPTPU12RAF03ACL010PUR Datasheet

Product Name // M12 Series A Code TPU Right-Angle **Overmould Flex Cable Connector 3 Contact Socket Pre-**Wired With 1M PUR Jacket Cable







// Product Description:

- M12 Series Right-Angle Overmould Flex Body Connectors
- 0 Water and dustproof to IP67 when mated with compatible connector
- Pin or Socket O
- 3, 4, 5, 8, 12 Contact (3, 8, 12 Contact are A Code, 4 Contact are choice of A Code or D Code, 5 Contact are choice of A Code or B Code)
- Overmould cable Termination with choice of lead lengths and choice of PVC or PUR jacket cable, depending on part code
- O Choice of Sealing Caps available separately to maintain IP rating
- O Mate with M12 Series Inline Body and Panel Mount Connectors, depending on part code

General Information:

Product Display Title: M12 Series Right-Angle Overmould Flex Body Connectors

Product Family: Circular Automation Connectors

M12 Series **Product Series:**

CSA, ENEC, UL, VDE Approvals: TPU

Body Material: Cable Length:

Contact Type: Socket Contact Coupling Type: Screw

4A **Current Max:** Diameter Over Coupling Ring Mm: 20mm

Function: Right Angle Flex Connector Single Ended Cable

Ip Rating: **IP67** +80°C Max Operating Temperature:

Min Operating Temperature: -25°C **Number Of Contacts:** 3 Contacts Pin Layout Code: A Code Sheath Material: PUR M12 x 1

Thread Size: Voltage Max: 250V

// Product PDF Links // Product 3D CAD Model Links

PXPTPU12RAF03ACL010PUR3D CAD M