


# RFNA4JFHMFB Datasheet

## Product Name // N Jack Straight 4 Hole Flange RF Connector

[View Product Page](#)

\* Representative product image only



### // Product Description:

- ⊗ N Jack Straight 4 Hole Flange RF Connector
- ⊗ Maximum Voltage: 500V
- ⊗ Temperature range: -55°C to +155°C
- ⊗ Frequency range: 0GHz - 18GHz
- ⊗ VSWR:
- ⊗ Dielectric withstanding Voltage: >1500V
- ⊗ Impedance: 50Ohm
- ⊗ Body Material: Stainless Steel Passivation
- ⊗ Contact Material: Beryllium Copper

### // General Information:

Product Display Title:	N Type Series Pin without Extended PTFE 4 Hole Flange
Product Family:	Radio Frequency Connectors
Product Series:	N Type Series
Body Length:	19.00mm
Body Material:	Stainless Steel Passivation
Centre Contact Retention Force:	>26.7N
Contact Pin Material:	Beryllium Copper
Min Coupling Torque:	0.80Nm
Max Coupling Torque:	1.10Nm
Dielectric Withstanding Voltage:	>1500V
Durability:	>500 cycles
Flange Mount Length:	17.50mm
Function:	Female Flange Mount RF Connector
Impedance:	50Ohm
Insulation Resistance:	>5000MOhm
Insulator:	Adapter ASTM D 1710 & PEI
Max Operating Temperature:	+155°C
Min Operating Temperature:	-55°C
Mount Hole Distance:	12.70mm
Min Operating Frequency:	0GHz
Max Operating Frequency:	18GHz
Pin Diameter:	1.50mm
Pin Length:	2.00mm
Thread Size:	5/8 24UNEF 2A
Voltage Max:	500V
Vswr:	<1.30

#### // Product PDF Links

[N Type Series Product Datasheet](#)

#### // Product 3D CAD Model Links

[RFNA4JFHMFB3D CAD Model](#)