


RFTERM240P1W Datasheet

Product Name // 2.40mm Plug Termination (1W)

[View Product Page](#)



// Product Description:

- ⊕ 2.40mm Plug Termination (1W)
- ⊕ Maximum Voltage: 335V
- ⊕ Temperature range: -40°C to +85°C
- ⊕ Frequency range: 0GHz - 50GHz
- ⊕ VSWR:
- ⊕ Dielectric withstanding Voltage: >750V
- ⊕ Impedance: 50Ohm
- ⊕ Body Material: Stainless Steel Passivation
- ⊕ Contact Material: Beryllium Copper

// General Information:

Product Display Title:	RF Termination Series 2.40mm
Product Family:	Radio Frequency Connectors
Product Series:	RF Termination Series
Average Power:	<1W
Body Length:	13.70mm
Body Material:	Stainless Steel Passivation
Centre Contact Retention Force:	>26.7N
Contact Pin Material:	Beryllium Copper
Dielectric Withstanding Voltage:	>750V
Durability:	>500 cycles
Function:	Male RF Termination
Impedance:	50Ohm
Insulation Resistance:	>5000MOhm
Insulator:	UNFILLED ULTEM 1000/PEI
Max Operating Temperature:	+85°C
Min Operating Temperature:	-40°C
Min Operating Frequency:	0GHz
Max Operating Frequency:	50GHz
Voltage Max:	335V
Vswr:	<1.30

// Product PDF Links

[RF Termination Series Product...](#)

// Product 3D CAD Model Links

[RFTERM240P1W3D CAD Model](#)