


**Product Name // TNCA Jack Straight 4 Hole Flange RF Connector**

[View Product Page](#)



**// Product Description:**

<ul style="list-style-type: none"> <li>⊕ TNCA Jack Straight 4 Hole Flange RF Connector</li> <li>⊕ Maximum Voltage: 500V</li> <li>⊕ Temperature range: -65°C to +165°C</li> <li>⊕ Frequency range: 0GHz - 18GHz</li> <li>⊕ VSWR:</li> </ul>	<ul style="list-style-type: none"> <li>⊕ Dielectric withstanding Voltage: &gt;1500V</li> <li>⊕ Impedance: 50Ohm</li> <li>⊕ Body Material: Stainless Steel Passivation</li> <li>⊕ Contact Material: Beryllium Copper</li> </ul>
--	--

**// General Information:**

Product Display Title:	TNCA Series Socket 4 Hole Flange
Product Family:	Radio Frequency Connectors
Product Series:	TNCA Series
Body Length:	18.90mm
Body Material:	Stainless Steel Passivation
Centre Contact Retention Force:	>26.7N
Contact Pin Material:	Beryllium Copper
Min Coupling Torque:	0.80Nm
Max Coupling Torque:	1.10Nm
Dielectric Withstanding Voltage:	>1500V
Durability:	>500 cycles
Flange Mount Length:	12.70mm
Function:	Female Flange Mount RF Connector
Impedance:	50Ohm
Insulation Resistance:	>5000MOhm
Insulator:	Adapter ASTM D 1710
Max Operating Temperature:	+165°C
Min Operating Temperature:	-65°C
Mount Hole Distance:	8.60mm
Min Operating Frequency:	0GHz
Max Operating Frequency:	18GHz
Socket Diameter:	0.91mm
Thread Size:	7/16 28UNEF 2A
Voltage Max:	500V
Vswr:	<1.30

**// Product PDF Links**

[TNCA Series Product Datasheet](#)

**// Product 3D CAD Model Links**

[RFTNCAA4JCCF3D CAD Model](#)