


RFTNCAA4JCCMF Datasheet

Product Name // TNCA Jack Straight 4 Hole Flange RF Connector

[View Product Page](#)



// Product Description:	
<ul style="list-style-type: none"> TNCA Jack Straight 4 Hole Flange RF Connector Maximum Voltage: 500V Temperature range: -65°C to +165°C Frequency range: 0GHz - 11GHz VSWR: 	<ul style="list-style-type: none"> Dielectric withstanding Voltage: >1500V Impedance: 50Ohm Body Material: Stainless Steel Passivation Contact Material: Beryllium Copper

// General Information:	
Product Display Title:	TNCA Series Pin without Extended PTFE 4 Hole Flange
Product Family:	Radio Frequency Connectors
Product Series:	TNCA Series
Body Length:	18.90mm
Body Material:	Stainless Steel Passivation
Centre Contact Retention Force:	>26.7N
Contact Pin Material:	Beryllium Copper
Min Coupling Torque:	0.80Nm
Max Coupling Torque:	1.10Nm
Dielectric Withstanding Voltage:	>1500V
Durability:	>500 cycles
Flange Mount Length:	12.70mm
Function:	Female Flange Mount RF Connector
Impedance:	50Ohm
Insulation Resistance:	>5000MOhm
Insulator:	Adapter ASTM D 1710
Max Operating Temperature:	+165°C
Min Operating Temperature:	-65°C
Mount Hole Distance:	8.60mm
Min Operating Frequency:	0GHz
Max Operating Frequency:	11GHz
Pin Diameter:	1.50mm
Pin Length:	2.00mm
Pin Slot Width:	0.20mm
Thread Size:	7/16 28UNEF 2A
Voltage Max:	500V
Vswr:	<1.30

// Product PDF Links

[TNCA Series Product Datasheet](#)

// Product 3D CAD Model Links

[RFTNCAA4JCCMF3D CAD Model](#)